

# THERMOMETER CALIBRATOR

Model :TC-424

ISO-9001, CE, IEC1010



\* Function :

1. Thermocouple calibrator ( source ).
2. Thermocouple thermometer.
3. Pt100 calibrator ( source )
4. Pt100 thermometer ( measurement ).
5. 400 ohm resistance calibrator ( source )
6. 400 ohm resistance measurement.
7. DC mV calibrator ( source ).
8. DC mV measurement.

\* Type K thermocouple : -200.0 to 1370.0 oC

\* Type J thermocouple : -200.0 to 1200.0 oC

\* Type T thermocouple : -200.0 to 400.0 oC

\* Type R thermocouple : 0 to 1760 oC

\* Type E thermocouple : -200.0 to 1000.0 oC

\* Type S thermocouple : 0 to 1760 oC

\* Pt 100 : 0 to 850.0 oC

\* Resistance: 0 to 400.0 ohm.

\* DC mV : -10.00 mV to +110.00 mV.

\* Temp. unit : oC/oF.

\* Power: 1.5V (UM-3/AA)battery x 6 PCs or  
DC 9V adapter in.

\* Optional type K Temp. probes :

TP-01, TP-02A , TP-03, TP-04, TP-05.

 Lutron



**LUTRON ELECTRONIC**

***The Art of Measurement***