

HI97701

Free Chlorine Portable Photometer

- **Advanced LED optical system**
 - LEDs have a much higher luminous efficiency, providing more light while using less power. They also produce little heat, which could otherwise affect electronic stability.
- **CAL Check™**
 - Validate the performance of the instrument at any time and apply a user calibration using CAL Check cuvettes made with NIST traceable standards. The CAL Check screen guides the user step-by-step through the validation process and user calibration
- **Auto logging**
- **GLP**
 - Review of the last calibration date.
- **On-screen tutorial mode with animations**
 - The built in Tutorial mode guides users step-by-step through the measurement process.
- **Waterproof and floating IP67 case**
- **Auto-shut off**
 - Automatic shut off after 15 minutes of inactivity and 30 minutes before a read measurement.
- **Battery status indicator**
 - Indicates the amount of battery life left.
- **Built-in timer**
 - Display of time remaining before a measurement is taken. Ensures that all readings are taken at the appropriate reaction intervals for the test being performed.
- **Error messages**
 - Messages on display alerting to problems including no cap, high zero, and standard too low.
- **Units of measure**
 - Appropriate unit of measure is displayed along with reading.



Specifications

HI97701 Free Chlorine

Measurement	Range (all methods)	0.00 to 5.00 mg/L (as Cl ₂)
	Resolution (all methods)	0.01 mg/L
	Accuracy @25°C (77°F) (all methods)	±0.03 mg/L ±3% of reading at 25 °C
Measurement System	Method	Adaptation of the EPA DPD method 330.5
	Light Source	light emitting diode
	Bandpass filter	525 nm
	Bandpass filter bandwidth	8 nm
	Bandpass filter wavelength accuracy	±1.0 nm
Additional Specifications	Light Detector	silicon photocell
	Cuvette type	round 24.6 mm diameter (22 mm inside)
	Auto logging	50 readings
	Display	128 x 64 pixel B/W LCD with backlight
	Auto-off	after 15 minutes of inactivity (30 minutes before a READ measurement)
	Battery type / Life	alkaline 1.5 V AA (3) / > 800 measurements (without backlight)
	Environment	0 to 50°C (32 to 122°F); 0 to 100% RH, non-serviceable
	Dimensions	142.5 x 102.5 x 50.5 mm (5.6 x 4.0 x 2.0")
	Weight	380 g (13.4 oz.)

Ordering Information

HI97701 is supplied with sample cuvettes (2), sample caps (2), plastic stoppers (2), 1.5V AA batteries (3), instrument quality certificate and instruction manual.

CAL Check standards and testing reagents sold separately

HI97701C includes photometer, CAL Check standards, sample cuvettes (2), sample caps (2), plastic stoppers (2), 1.5V AA batteries (3), cuvette wiping cloth, scissors, instrument quality certificate, instruction manual and HI7101412 rigid carrying case.

Reagents sold separately

Reagents and Standards

HI97701

HI97701-11 CAL Check standard cuvettes for free and total chlorine

HI93701-01 free chlorine powder reagent (100 tests)

HI93701-03 free chlorine powder reagent (300 tests)

HI93701-F free chlorine liquid reagent (300 tests)